



muxxlube.de

# Σ 900 0W40



**MUXX ÖL**

Frankenhauserstraße 15, 12249 Berlin,  
Deutschland

Telefon: +49 (0)30 61633942

Muxx Oil GmbH service@muxxlube.com



## Description

- Formulated with advanced double ester technology. Suitable for Asian climates and road conditions, especially dedicated for racing cars.
- Lubricating film with strong protection to maintain stability and low evaporation loss under high temperature environments and high transmission conditions.
- Outstanding starting performance and optimum transmission performance.
- Stable oil pressure to maximize engine operation.


## Performance Levels

Exceed all the OEM requirements

Test Item	Typical Spec.	Typical Result
Density at 15°C	Report	0.856
Kinematic Viscosity at 100 °C , cSt	12.5-16.3	14.82
Kinematic Viscosity at 40°C , cSt	Report	89.27
Viscosity Index	Min. 170	175
Flash Point (Open)°C	Min. 200	231
TBN, mg/KOH/g	Min. 10.0	10.2
Pour Point,°C	Max. -35	-45
Color	Report	2.5
CCS-30°C	Max. 6600	
HTHS 150°C, cP	≥3.5	

\*The Above Test Result is subject for change and for reference only

## Spider diagrams



## SUPER SPEED!

Suitable for racing with wild speed!

