



muxxlube.de

Σ900 5W40



MUXX ÖL

Frankenhauserstraße 15, 12249 Berlin,

Deutschland

Telefon: +49 (0)30 61633942

Muxx Oil GmbH service@muxxlube.com



Description

- Formulated with advanced double ester technology. Suitable for Asian climates and road conditions, especially dedicated for racing cars.
- Lubricating film with strong protection to maintain stability and low evaporation loss under high temperature environments and high transmission conditions.
- Outstanding starting performance and optimum transmission performance.
- Stable oil pressure to maximize engine operation.


Performance Levels

Exceed all the OEM requirements

Test Item	Typical Spec.	Typical Result
Density at 15°C	Report	0.8583
Kinematic Viscosity at 100 °C, cSt	12.5-16.3	14.75
Kinematic Viscosity at 40 °C, cSt	Report	89.05
Viscosity Index	Min. 165	173
Flash Point (Open)°C	Min. 200	232
TBN, mg/KOH/g	Min. 10.0	10.2
Pour Point, °C	Max. -30	-42
Color	Report	2.5
CCS-30°C	Max. 6600	5510
HTHS 150°C, cP	≥3.7	3.9

*The Above Test Result is subject for change and for reference only

Spider diagrams



SUPER SPEED!

Suitable for racing with wild speed!

