



German Quality

MUXX OIL GmbH
 15 Frankenhäuser St., 12249 Berlin,
 Germany.
 Office: +49 (0)30 61633942
 Website: www.muxxlube.de
 E-Mail: service@muxxlube.com

Description

-C 400 SN 10W40 is a high performance fuel saving semi synthetic oil for gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is NOT suitable for diesel engines with a Diesel Particle Filter (DPF).

-C 400 SN 10W40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Performance Levels

API SN ACEA A3/B3 MB 229.1 VW 502/505

Test Item	Typical Spec.	Typical Result
SAE Grade		10W40
Density @15°C	kg/m ³	859
Kin. Viscosity @40°C	mm ² /s	96.06
Kin. Viscosity @100°C	mm ² /s	14.51
Viscosity Index		155
Flash Point COC	°C	233
Pour Point	°C	-37
Total Base Number	mgKOH/g	7.7
Color		L2.5



EELQMS

EUROPEAN ENGINE
 LUBRICANTS QUALITY
 MANAGEMENT SYSTEM



*The Above Test Result is subject for change and for reference only

