



600 SN 5W30



German Quality

MUXX OIL GmbH
15 Frankenhäuser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- D 600 SN 5W30 is synthetic multi-grade engine oil specially formulated to meet the superior performance and fuel efficiency requirements of modern engines requiring low viscosity oils. Enhanced oil flow and film strength give essential protection during start-up. Advanced additive technology provides long term benefits such as reducing wear on critical valve-train components in modern engines.
- D 600 SN 5W30 is recommended for the latest petrol and diesel engines of passenger cars, including turbo and supercharged version engines which require low viscosity 5W/30 oil.
- D 600 SN 5W30 can be used for most modern engines, and it meets the API SL standard requirement.

Performance Levels

API SN

Test Item	Typical Spec.	Typical Result
SAE Grade		5W30
Density @15°C	kg/m ³	861
Kin. Viscosity @40°C	mm ² /s	67.4
Kin. Viscosity @100°C	mm ² /s	10.65
Viscosity Index		148
Viscosity CCS @-30°, max.	cP	6025
Flash Point COC	°C	220
Pour Point	°C	-33
Total Base Number	mgKOH/g	7.1
Color		1.0

*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

