



100 4T 10W40



German Quality

MUXX OIL GmbH
15 Frankenhäuser St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

- E 100 4T 10W40 is manufactured from high quality mineral oil and an advanced additive system. It is designed primarily for petrol engines, but may also be used in older diesel units. E 100 4T 10W40 will keep engine components clean and deposit-free, as well as provide protection against wear, rust and corrosion. This grade is ideal for engines which start to suffer from high oil consumption or low oil pressure.
- E 100 4T 10W40 is recommended for passenger cars as well as light duty diesel engines. E 100 4T 10W40 viscosity is the ideal range for the daily-use vehicles which require quick oil flow performance in certain weather conditions. It can be used for most OEM car manufactures without any emission requirement.

Performance Levels

API SL JASO MA

Test Item	Typical Spec.	Typical Result
SAE Grade		10W40
Density @15°C	kg/m ³	861
Kin. Viscosity @40°C	mm ² /s	101.05
Kin. Viscosity @100°C	mm ² /s	14.83
Viscosity Index		153
Viscosity CCS @-20°	cP	6033
Flash Point COC	°C	230
Pour Point	°C	-39
Total Base Number	mgKOH/g	6.41
Color		2.0

*The Above Test Result is subject for change and for reference only

