



800
0W40



German Quality

MUXX OIL GmbH
15 Frankenhauer St., 12249 Berlin,
Germany.
Office: +49 (0)30 61633942
Website: www.muxxlube.de
E-Mail: service@muxxlube.com

Description

Fully Synthetic Passenger Car Motor Oil

R 800 0W40 is a high performance fuel saving fully synthetic engine oil to be used in gasoline- and diesel engines of the latest generation passenger car and light vans with or without turbo compressor.

R 800 0W40 is based on high performance fully synthetic base oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- High viscosity index in a wide range of ambient conditions.
- Low temperature properties, to ensure a smooth cold start.

Performance Levels

API SN ACEA A3/B4 VW 502.00/505.00 Porsche A40 BMW LL-01 Renault RN0700/0710
MB 229.3 MB 229.5 Ford M2C937-A

Test Item	Typical Spec.	Typical Result
SAE Grade		0W40
Density @15°C	kg/m ³	842
Kin. Viscosity @40°C	mm ² /s	77
Kin. Viscosity @100°C	mm ² /s	14.2
Viscosity Index		185
Viscosity CCS @-30°, max.	cP	6200
Flash Point COC	°C	>201
Pour Point	°C	-42
Total Base Number	mgKOH/g	10

*The Above Test Result is subject for change and for reference only



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

