



**800 A5**  
**0W30**



German Quality

MUXX OIL GmbH  
15 Frankenhauer St., 12249 Berlin,  
Germany.  
Office: +49 (0)30 61633942  
Website: [www.muxxlube.de](http://www.muxxlube.de)  
E-Mail: [service@muxxlube.com](mailto:service@muxxlube.com)

## Description

-Fully Synthetic Passenger Car Motor Oil

-R 800 A5 0W30 is a very high performance fuel saving oil based on fully Synthetic for use in the very latest gasoline and diesel engines of passenger cars equipped with exhaust particle filters. Designed to meet the requirements for the new Ford M2C950-A specification for diesel engines. Also suitable for the latest Peugeot/Citroën vehicles that require PSA B71 2312.

-R 800 A5 0W30 is formulated with high quality synthetic base stocks in combination with special selected additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Excellent high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- Excellent dispersancy and detergency level.
- Very high viscosity index.

## Performance Levels

ACEA C2

Ford M2C950-A

PSA B71 2312

Test Item	Typical Spec.	Typical Result
SAE Grade		0W30
Density @15°C	kg/m <sup>3</sup>	841
Kin. Viscosity @40°C	mm <sup>2</sup> /s	46
Kin. Viscosity @100°C	mm <sup>2</sup> /s	9.4
Viscosity Index		194
Viscosity CCS @-30°, max.	cP	5200
Flash Point COC	°C	>201
Pour Point	°C	-42
Total Base Number	mgKOH/g	8.4
Sulphated Ash	%Wt	0.79

\*The Above Test Result is subject for change and for reference only



**EELQMS**  
EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

